



產品規範書
specification

PRODUCT NAME

產品名稱

BOPP PACKAGING TAPE
BOPP包裝膠帶

修訂日期 Date 2022/8/24

型號 Model No. 165

MAKER 製表

基材 Backing BOPP

姚佳紋

膠系 Adhesive 壓克力油膠 Acrylic Emulsion

顏色 Color 印刷 Print

特性

Feature ■

黏性強、抗壓力佳、耐候性佳。

High adhesion, high tensile strength and weather-resistance.

項目

標準規範

檢驗方式

Item

Standard Value

Test Method

外觀

不能打皺、色差、空隙
No wrinkle, interval
and

目視

厚度 (mm)

Thickness

0.065±0.002

PSTC-133

應用

Application ■

適用一般包裝封箱固定用，且廣泛用於自動封箱機器。

Widely used for common sealing or light weight packaging, also widely used for automatic sealing machine.

黏著力 (kg/in)

Peel adhesion

0.61

PSTC-101

保持力 (min)

Holding power

1440↑

PSTC-7

抗拉強度 (kg/in)

Tensile Strength

5.1↑

PSTC-131

延伸率 (%)

Elongation

100↑

PSTC-131

備註

Remark ■

* 客戶需依其實際操作需求與目的，進行產品測試與確認，或通知本公司，以提供進一步說明與服務。

Customers need to test and confirm products for the actual operational requirement and purpose or inform us to supply the further introduction and service.

* 本表僅提供參考，不可作為驗收標準。

Above information is for reference only and should not be as inspection standard.

* 以上數據資料皆為在室溫23±2°C及濕度50±5%所測試結果。

Above information are completed under room temperature 23±2°C and humidity 50±5%.